

**(19) World Intellectual Property
Organization
International Bureau**



(43) International Publication Date
2 June 2005 (02.06.2005)

PCT

(10) International Publication Number
WO 2005/050134 A1

(51) International Patent Classification⁷: G01B 21/04

(72) Inventors; and

(21) International Application Number:
PCT/GB2004/004830

(75) **Inventors/Applicants (for US only):** **MCMURTRY, David, Roberts** [GB/GB]; Park Farm, Stancombe, Dursley, Gloucestershire GL11 6AT (GB). **MC FARLAND, Geoff** [GB/GB]; The Manse, 22 Church Road, Upper Cam, Dursley, Gloucestershire GL11 5PG (GB). **JONAS, Keyvn, Barry** [GB/GB]; 18 Sunningdale, Clifton, Bristol BS8 2NF (GB).

(22) International Filing Date:
15 November 2004 (15.11.2004)

(25) Filing Language: English

(74) Agents: LELAND, Emma, Clare et al.; Renishaw plc, Patent Department, New Mills, Wotton-under-Edge, Gloucestershire GL12 8JR (GB).

(26) Publication Language: English


(30) Priority Data:
0326532.9 13 November 2003 (13.11.2003) GB

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DU, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,

(71) Applicant (for all designated States except US): REN-ISAW PLC [GB/GB]; New Mills, Wotton-under-Edge, Gloucestershire GL12 8JR (GB).

[Continued on next page]

(54) Title: METHOD OF ERROR COMPENSATION IN A COORDINATE MEASURING MACHINE WITH AN ARTICULATING PROBE HEAD



(57) Abstract: A method of error compensation for measurements taken using a co-ordinate positioning apparatus comprising an articulating probe head having a surface detecting device. The surface detecting device is rotated about at least one axis of the articulating probe head during measurement. The method comprises the steps of: determining the stiffness of the whole or part of the apparatus; determining one or more factors which relate to the load applied by the articulating probe head at any particular instant, and determining the measurement error at the surface sensing device caused by the load.



MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

— *of inventorship (Rule 4.17(iv)) for US only*

- (84) **Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE,

Published:

— *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.